

Indian Journal of Pure & Applied Physics Vol. 58, May 2020, pp. 392-396



Measurement of (n,γ) reaction cross section of ¹⁸⁶W-isotope at neutron energy of 20.02±0.58 MeV

Mayur Mehta^{a,b*}, N L Singh^b, R Makwana^b, P V Subhash^c, S V Suryanarayana^d, S Parashari^b, Rakesh Chauhan^b, R K Singh^b, H Naik^e, S Mukherjee^b, B Soni^b, S Khirwadkar^a, J Varmuza^f & K Katovsky^f

^aInstitute for Plasma Research, Gandhinagar 382 428, India ^bDepartment of Physics, The M S University of Baroda 390 002, India

^cITER-India, Gandhinagar 382 428, India

^dNuclear Physics Division, Bhabha Atomic Research Centre, Mumbai 400 085, India

^eRadiochemistry Division, Bhabha Atomic Research Centre, Mumbai 400 085, India

^fDepartment of Electrical Power Engineering, Brno University of Technology, Brno 61600, Czech Republic

Received 4 May 2020

The cross-section of $^{186}W(n,\gamma)^{187}W$ reaction has been measured at an average neutron energy of 20.02±0.58 MeV by using activation technique. The $^{27}Al(n,\alpha)^{24}Na$ and $^{115}In(n,n')^{115m}In$ reactions have been used for absolute neutron flux measurement. Theoretically the reaction cross-sections have been calculated by using the TALYS-1.9 code. The results from the present work and the EXFOR based literature data have been compared with the evaluated data and calculated data from TALYS-1.9 code.

Keywords: Tungsten, Plasma facing material, ¹⁸⁶W(n,γ)¹⁸⁷W reaction cross-section, ²⁷Al(n,α)²⁴Na and ¹¹⁵In(n,n')^{115m}In monitor reactions, ⁷Li(p,n)⁷Be reaction, γ -ray spectrometric technique, TALYS-1.9

1 Introduction

Tungsten is considered to be a prime plasma facing material used as divertor component in ITER like fusion reactor. For the design and safety of nuclear reactors, accurate data of reaction cross-section needed for materials used in reactors¹⁻⁴. There are large discrepancies and deficiencies of the neutron induced reaction cross-section data in a range from 5 to 20 MeV. This work provides the detail measurement of $^{186}W(n,\gamma)^{187}W$ reaction cross-section at an average neutron energy (E_n) of 20.02±0.58 MeV using activation and off-line γ -ray spectrometric technique. Theoretically the reaction cross-section was predicted by the nuclear modular codes TALYS-1.9⁵. The experimentally measured crosssection was compared with Experimental Nuclear Reaction Data (EXFOR)⁶ and Evaluated Nuclear Data File $(ENDF)^7$.

2 Experimental Details

The experimental work was carried out at 6 meter height of beam line of Pelletron facility at Tata Institute of Fundamental Research-Bhabha Atomic Research Center (TIFR-BARC)-Mumbai. The neutrons of desired energy was generated by the ${}^{7}\text{Li}(p,n){}^{7}\text{Be}$ reaction^{8,9} using 14UD BARC-TIFR Pelletron facilities at Mumbai, India. The proton beam energy of 22 MeV was passed through Tantalum–Lithium–Tantalum (Ta-Li-Ta) stack to generate neutron energy of 20.02±0.58 MeV. During the experiment, the beam current was about 150-170 nAmps. A natural Li metal foil of thickness 6.8 mg/cm² was wrapped between Ta foils of thickness 3.2 mg/cm² in front and 0.025 mm in the back side. According to SRIM ¹⁰ calculation, the degradation of proton energy was ~50 keV.

Plansee natural tungsten (W) metal sample of thickness 3 mm and size 10×10 mm was used for irradiation. Aluminum (Al) and indium (In) foils of thickness 0.1 mm and 10×10 mm size were used as flux monitor via ${}^{27}\text{Al}(n,\alpha){}^{24}\text{Na}$ and ${}^{115}\text{In}(n,n'){}^{115\text{m}}\text{In}$ reactions. Tungsten and monitor samples (Al and In) were wrapped with 0.025 mm thick aluminum foil to avoid contamination during the irradiation. In-W-Al stack was placed at 0° in forward direction to the beam at a distance of distance of 2.1 cm. To determine accurate value and minimize the error in neutron flux incident on the target sample Al and In

^{*}Corresponding author (E-mail: mayur@ipr.res.in)

foils were used as flux monitors. The nuclear spectroscopic data of reaction products are given in Table 1 retrieved from Ref.¹¹. A schematic diagram of experimental set up was shown in Fig. 1.

The stack was irradiated for 5-6 h and then cooled for sufficient hours. Then the irradiated samples were mounted on Perspex plates for γ -ray activity measurement. Pre-calibrated 80 cm³ High Purity Germanium (HPGe) detector was used for the γ -ray counting of the irradiated samples. To avoid the summation effect, the mounted samples were placed at a suitable distance from the detector cap. The resolution of the detector system had a full-width at half-maximum of 1.8 keV at 1.332 MeV γ -ray photopeakof ⁶⁰Co. The energy and efficiency calibration was performed by using standard ¹⁵²Eu multi-gamma source, maintaining the same geometry¹².

3 Data Analysis

3.1 Measurement of average neutron energy and neutron flux

The spectrum averaged neutron energy was calculated by using the following equation¹³:

$$E_{\text{mean}} = \frac{\int_{\text{Eps}}^{\text{E}_{\text{max}}} E_{i} \Phi_{i} dE}{\int_{\text{Eps}}^{\text{E}_{\text{max}}} \Phi_{i} dE} \qquad \dots (1)$$

where, E_{mean} is effective mean energy E_{ps} is starting of neutron energy peak, E_{max} is maximum neutron energy, E_i is energy bin and Φ_i is neutron flux of energy bin E_i .

Figure 2 represents the continuous neutron spectrum for Eproton= 22 MeV. A detailed discussion on the generation of neutron spectra is also provided in our earlier publications¹⁴⁻¹⁷. The reported crosssections from the neutron spectrum were found in agreement with the literature and theoretical data for the respective case of study. One of the collaborators Katovsky (Department of Electrical Power Engineering, Brno University of Technology, Brno, Czech Republic) performed MCNP6.1 calculations for the neutron spectrum generation using the defined

geometry of the target assembly for 22 MeV energy protons. The simulated spectra were found in agreement with the theoretical reproductions from the previous works¹⁸⁻²⁰. Minor discrepancies, however, may be found among the compared results. A rough estimation of the neutron flux using the simulated spectra were found in agreement with the flux used in the present work within the uncertainty of $\approx 3\%$. The uncertainty due to the neutron flux was already used in the weighted cross-sections of monitor reaction from EXFOR library. At this point, we cannot re-calculate the entire calculations as the results from the simulate spectra lies within the range of present



Fig. 1 — Schematic diagram of irradiation set up.



Fig. 2 — Neutron spectrum for E_{proton} = 22 MeV with low energy tail.

Table 1— Nuclear spectroscopic data of reaction products from Ref. ¹⁹ .								
Reaction	Threshold energy (MeV)	Half-life	Decay mode	γ-ray energy (keV)	γ-ray abundance (%)			
115 In(n,n') 115m In		4.486h	IT (95%) β ⁻ (5%)	336.24	45.83			
27 Al(n, α) 24 Na	3.249	14.959h	β ⁻ (100%)	1368.63	100			
186 W(n, γ) 187 W		23.72h	β ⁻ (100%)	479.531	21.8			
				685.774	27.3			

results. The recorded neutron spectrum on target sample has a long tail in the lower energy region. In order to measure the reaction cross-section at the main peak of neutron energy, the tailing correction has been done by using the method given in literature¹⁷. Figure



Fig. 3 — (a) Recorded γ -ray spectra of products from the monitor reactions and (b) recorded γ -ray spectra of products from the monitor reactions.



Fig. 4 — Recorded $\gamma\text{-ray}$ spectrum of reaction products from the $^{186}W(n,\gamma)^{187}W$ reaction.

3(a,b) and Figure 4 show γ -ray spectra of monitor reaction and sample reaction products.

The neutron flux was determined by ${}^{27}Al(n,\alpha){}^{24}Na$ $(t_{1/2}=14.959)$ hour, E_v=1368.63 keV) and 115 In(n,n') 115m In(t_{1/2}=4.486 hour, E_y=336.24 keV) monitor reactions. In order to calculate the neutron flux incident on the sample, the spectrum averaged cross-section was calculated for the monitor reaction by using the available data from EXFOR ⁶. The spectrum averaged cross-section was calculated by using equation:

$$\sigma_{av} = \frac{\int_{E_{th}}^{E_{max}} \sigma_i \Phi_i dE}{\int_{E_{th}}^{E_{max}} \Phi_i dE} \qquad \dots (2)$$

where, σ_{av} is spectrum averaged cross-section, E_{th} is threshold energy of the monitor reaction, Emax is maximum neutron energy, σ_i is cross-section of monitor reaction at energy E_i from EXFOR data, Φ_i is neutron flux of energy bin E_i.

The γ -ray spectrum of monitors is shown in Fig. 3. The spectrum averaged cross-section and the neutron flux measured by using the activation formula is given in Table 2.

$$\Phi = \frac{A_{\gamma\lambda}(CL/_{LT})}{N\sigma_{av}I_{\gamma}\varepsilon(1-e^{-\lambda t}i)(1-e^{-\lambda t}c)e^{-\lambda CL}} \qquad \dots (3)$$

where, A_{γ} is number of photo peak counts, λ is decay constant of reaction (sec⁻¹), N is number of target atoms, σ_{av} is spectrum averaged cross-section, I_{v} is absolute γ -ray intensity, ϵ is efficiency of the γ -ray of interest, t_i is time of sample irradiation(sec), t_c is cooling time (between the end of irradiation and start of counting in sec), CL is clock time and LT is live time for counting and CL/LT term is used for dead time correction.

3.2 Measurement of ${}^{186}W(n,\gamma){}^{187}W$ reaction cross-section The cross-section of ${}^{186}W(n,\gamma){}^{187}W$ reaction was measured by using photo peak activity of 479.531 and 685.774keV γ -ray of ¹⁸⁷W isotope. The equation used to measure the reaction cross-section is as follows:

$$\sigma = \frac{A_{\gamma}\lambda \left(\frac{CL}{LT}\right)}{N\Phi I_{\gamma}\epsilon \left(1 - e^{-\lambda t_{i}}\right)\left(1 - e^{-\lambda t_{c}}\right)e^{-\lambda CL}} \qquad \dots (4)$$

All terms in Eq. (4) have a significance meaning as in Eq. (3).

Т	able 2 — Spectrum average c	ross-section and measured ne	utron flux from monitor reaction	ions.
E _n (MeV)	Spectrum Average Cross-section (mb)		Neutron Flux (ncm ⁻² s ⁻¹)	
20.02±0.58	115 In(n,n') 115m In	27 Al(n, α) 24 Na	$115 In(n,n')^{115m} In$	27 Al(n, α) ²⁴ Na
	150.43	60.59	3.39×10^{6}	3.36×10^{6}

$E_n(\text{INEV})$		$W(\Pi,\gamma)$	w reaction cross-section (1		
20.02 ± 0.58	Measured	TALYS-1.9	ENDF/B-VIII.0	JEFF-3.3	JENDL-4.0
	0.3656 ± 0.031	0.4472	0.35834	0.4881	0.2526

4 Results and Discussion

As shown in Fig. 2, the neutron spectra have tail part in lower energy range. This low energy neutron tail part will cause contribute to the measured reaction cross-section. The experimentally measured crosssection of ${}^{186}W(n,\gamma){}^{187}W$ at neutron energy of 20.02±0.58 MeV is 0.5531 mb and the contribution due to low energy neutron tail part of spectrum is 0.1875 mb as calculated based on Ref.²¹. Thus for an average neutron energy of 20.02±0.58 MeV, after subtracting the contribution from the low energy neutron tail region, the actual experimentally obtained $^{186}W(n,\gamma)^{187}W$ cross-sections was found to be 0.3656 mb. Table 3 shows the comparison of experimentally measured reaction cross-section with theoretically predicated data by TALYS-1.9 and available literature data. Theoretically the reaction cross-section as a function of neutron energy (E_n) was calculated by TALYS-1.9 code using default parameters as well as by different parameters such as y-strength functions, nuclear level densities and nuclear model parameters etc. In present case we predict the reaction cross-section by considering different level density parameters such as constant temperature + Fermi gas model, Back-shifted Fermi gas model. Generalised super fluid model and Microscopic level densities options available as LD model-1 to LD model-6. Figure 5 shows the comparison of ${}^{186}W(n,\gamma){}^{187}W$ reaction cross-section with the previously measured data by different authors^{17,22-25} as well as literature data available in nuclear data library⁷ and the predicated values based on TALYS-1.9 code ⁵. From Table 3 and Fig. 5, it is observed that the cross-section of ${}^{186}W(n,\gamma){}^{187}W$ reaction is in excellent agreement with the evaluated data from ENDF/B-VIII.0 library and is in close agreement with TALYS-1.9 and JEFF-3.3 at the neutron energy of 20.02±0.58 MeV. It can also be seen from Fig. 5 that, present and literature data within the neutron energies of 2-24 MeV follow a close trend of the calculated values from TALYS-1.9



Fig. 5 — Comparison of ${}^{186}W(n,\gamma){}^{187}W$ reaction cross-section with literature data, evaluated data from different libraries and calculated values from TALYS-1.9 code.

code and evaluated data of ENDF/B-VIII.0 library but not of JEFF-3.3 library at lower neutron energy.

5 Conclusions

In present work, the cross-section of ${}^{186}W(n,\gamma){}^{187}W$ reaction was measured first time experimentally at the neutron energy of 20.02±0.58 MeV by using neutron activation method. The measured reaction cross-section of tungsten isotope was compared with the theoretically predicated data from TALYS-1.9 and data available in evaluated cross-section data libraries, which show a close agreement.

Acknowledgement

The authors would like to thank S C Sharma (BARC-TIFR Pelletron Facility) for his help in preparation of irradiation setup and to the staff of High Temperature Technologies Division, IPR for providing the target samples. The author also acknowledge to the staff of Neutronics lab, IPR for off-line measurements and analysis.

References

- 1 Pintsuk G, Comp Nucl Mater, 4 (2012) 551.
- 2 Nygren R E , Youchison D L , Wirth B D & Snead L L, *Fusion Eng Design*,109 (2016) 192.
- 3 Forrest R A, Fusion Eng Design, 81 (2006) 2143.
- 4 Wenrong Z, Hanlin L, Weixiang Y & Xialin Y, Compilation of measurement and evaluations of nuclear activation cross section for nuclear data applications, INDC (CPR)-16 (1989).
- 5 Koning A J, TALYS-1.9, A Nuclear reaction program, user's manual, NRG-1755 ZG Petten, The Netherlands (2018).
- 6 EXFOR, Cross Section Information Storage and Retrieval System (EXFOR), IAEA, Vienna, Austria, (http://www.nds.iaea.or.at/exfor/(online))
- 7 ENDF, Cross Section Information Storage and Retrieval System (EXFOR), IAEA, Vienna, Austria, https://www-nds.iaea.org/exfor/endf.htm(online)>
- 8 Poppe C H & Anderson J D, *Phys Rev C*, 14 (1976) 438.
- 9 Mashnik S G, Chadwick M B, H Hughes G, Little R C, Macfarlane R E, Waters L S & Young P G, ⁷Li(p, n) Nuclear data Library for Incident Proton Energies to 150MeV, arXiv: nuclth/00110666v117.
- 10 Ziegler J F, Nucl Instr Meth Phys Res B, 219-220 (2004) 1027.
- 11 National Nuclear Data Center, http://www.nndc .bnl. gov/nu dat2/index.jsp
- 12 Yerraguntla S S, Naik H, Karantha M, Ganesan S, Saraswatula S V & Nair S N P, *Radiochim Acta*, 106 (2018) 877.
- 13 Smith D L, et al., Corrections for Low Energy Neutrons by Spectral Indexing, retrieved from https://www.oecdnea.org/ science/docs/2005/nsc-wpec-doc2005-357.pdf.

- 14 Bhargav S, Siddharth P, Mukherjee S, Makwana R, Suryanarayana S V, Nayak B K, Naik H, Varmuza J & Katovsky K, *Eur Phys J Plus*, 300 (2020) 135.
- 15 Parashari S, Mukherjee S, Suryanarayana S V, Nayak B K, Makwana R, Singh N L & Naik H, *Phys Rev C*, 99 (2019) 044602.
- 16 Parashari S, Mukherjee S, Naik H, Suryanarayana S V, Makwana R, Nayak B K & Singh N L, *Eur Phys J A*, 51 (2019) 55.
- 17 Makwana R, Mukherjee S, Mishra P, Naik H, Singh N L, Mehta M, Katovsky K, Suryanarayana S V, Vansola V, Sheela Y S, Karkera M, Acharya R & Khirwadkar S, *Phys Rev C*, 96 (2017) 024608.
- 18 Liskien J H & Paulsen A, Atomic Data Nucl Data Table, 15 (1975) 57.
- 19 Meadows J W & Smith D L, Neutrons from Proton Bombardment of Natural Lithium, Argonne National Laboratory Report ANL-7983 (1972).
- 20 McNaughton M W, King N S P, Brady F P, Romero J L & Subramanian T S, *Nucl Instr Meth*, 130 (1975) 555.
- 21 Badwar S, Ghosh R, Lawriniang B M, Vansola V, Sheela Y S, Naik H, Naik Y, Suryanarayana S V, Jyrwa B & Ganesan S, *Appl Radiat Isot*, 129 (2017) 117.
- 22 Perkin J L, Oconnor L P & Coleman R F, *Proc Phys Soc*, 72 (1958) 505.
- 23 Magnusson G, Andersson P & Berquist I, *Physica Scripta*, 21 (1980) 21.
- 24 Valkonen M, Homberg P, Rieppo R, Keinaenen J K & Kantele J, *Phys Lett B*, 39 (1976) 625.
- 25 Schwerer O, Winkler-Rohatsch M, Warhanek H & Winkler G, *Nucl Phys A*, 264 (1976) 105.